

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KEZA	Power Supply	Outdoor Models				Indoor Models			
		R404A R507	R407A	R448A R449A	R407C	R404A R507	R407A	R448A R449A	R407C
KEZA007H8-*	S2D	208-230/1/60	7.6	7.6	7.6	-	-	-	-
	T3D	208-230/3/60	7.6	7.6	7.6	-	-	-	-
KEZA008H8-*	S2D	208-230/1/60	7.6	7.6	7.6	-	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	-	5.61	5.61	5.61
KEZA009H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA010H8-*	S2D	208-230/1/60	7.6	7.6	7.6	-	-	-	-
	T3D	208-230/3/60	7.6	7.6	7.6	-	-	-	-
	T4D	460/3/60	7.6	7.6	7.6	-	-	-	-
KEZA011H8-*	S2D	208-230/1/60	7.6	7.6	7.6	-	-	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	-	-	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	-	-	5.61	5.61
KEZA015H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA020H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	-	-	-
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	-	-	-
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	-	-
	T5D	575/3/60	7.6	7.6	7.6	7.6	-	-	-
KEZA025H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA030H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA035H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA040H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA045H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA050H8-*	S2D	208-230/1/60	7.6	7.6	7.6	7.6	-	5.61	5.61
	T3D	208-230/3/60	7.6	7.6	7.6	7.6	-	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	-	5.61	5.61
KEZA060H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA061H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	-	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	-	-	5.61	5.61
KEZA070H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA076H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA085H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	-	-	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	-	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	-	-	5.61
KEZA110H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	5.61	5.61	5.61
KEZA150H8-*	T3D	208-230/3/60	7.6	7.6	7.6	7.6	-	-	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	-	5.61
	T4D	460/3/60	7.6	7.6	7.6	7.6	-	-	5.61
	T5D	575/3/60	7.6	7.6	7.6	7.6	-	-	5.61

- = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Model KEZA	Power Supply	Outdoor Models			Indoor Models			
		R404A	R407A	R448A	R404A	R407A	R448A	
		R507		R449A	R507		R449A	
KEZA008L8-*	S2D	208-230/1/60	2.88	-	-	2.03	-	-
	T3D	208-230/3/60	2.88	-	-	2.03	-	-
KEZA010L8-*	S2D	208-230/1/60	2.93	2.91	2.92	2.10	-	-
	T3D	208-230/3/60	2.93	2.91	2.92	2.10	-	-
KEZA015L8-*	S2D	208-230/1/60	2.98	2.96	2.97	2.17	2.13	2.15
	T3D	208-230/3/60	2.98	2.96	2.97	2.17	2.13	2.15
KEZA020L8-*	S2D	208-230/1/60	3.1	3.08	3.08	-	-	-
	T3D	208-230/3/60	3.1	3.08	3.08	-	-	-
KEZA025L8-*	S2D	208-230/1/60	3.15	-	3.14	2.40	-	2.39
	T3D	208-230/3/60	3.15	3.13	3.14	2.40	-	2.39
	T4D	460/3/60	3.15	3.13	3.14	2.40	-	2.39
KEZA030L8-*	S2D	208-230/1/60	3.15	-	3.15	2.40	-	2.40
	T3D	208-230/3/60	3.15	3.15	3.15	2.40	-	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	-	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	-	2.40
KEZA035L8-*	S2D	208-230/1/60	3.15	-	3.15	-	-	-
	T3D	208-230/3/60	3.15	3.15	3.15	2.40	-	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	-	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	-	2.40
KEZA045L8-*	S2D	208-230/1/60	3.15	-	3.15	2.40	-	-
	T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
KEZA055L8-*	S2D	208-230/1/60	3.15	-	3.15	-	2.40	2.40
	T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
KEZA060L8-*	T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
KEZA075L8-*	T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
KEZA085L8-*	T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
	T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
KEZA100L8-*	T3D	208-230/3/60	3.15	-	3.15	-	2.40	2.40
	T4D	460/3/60	3.15	-	3.15	-	2.40	2.40
	T5D	575/3/60	3.15	-	3.15	-	2.40	2.40
KEZA130L8-*	T3D	208-230/3/60	3.15	-	3.15	2.40	-	2.40
	T4D	460/3/60	3.15	-	3.15	2.40	-	2.40
	T5D	575/3/60	3.15	-	3.15	2.40	-	2.40
KEZA150L8-*	T3D	208-230/3/60	3.15	-	3.15	-	-	-
	T4D	460/3/60	3.15	-	3.15	-	-	-
	T5D	575/3/60	3.15	-	3.15	-	-	-
KEZA170L8-*	T3D	208-230/3/60	-	-	3.15	-	-	-
	T4D	460/3/60	-	-	3.15	-	-	-
	T5D	575/3/60	-	-	3.15	-	-	-

- = Non-compliant model

web: www.k-rp.com/kez
email: smcu@k-rp.com
call: 1-844-893-3222 x521

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KEH	Outdoor Models				Indoor Models			
	R404A	R507	R407A	R448A R449A	R404A	R507	R407A	R448A R449A
KEHA006M8- * S2D	7.60		-	7.60	-	-	-	-


- = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KEH	Outdoor Models				Indoor Models			
	R404A	R507	R407A	R448A R449A	R404A	R507	R407A	R448A R449A
KEHA008L6- * S2D	2.85		-	-	1.99	-	-	-

- = Non-compliant model



web: www.k-rp.com/keh
email: smcu@k-rp.com
call: 1-844-893-3222 x521

Annual Walk-In Energy Factor Ratings - COPELAND - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Unit Model KESA	Power Supply	Outdoor Models				Indoor Models			
		R404A	R407A	R448A	R407C	R404A	R407A	R448A	R407C
		R507		R449A		R507		R449A	
050H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
050H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
050H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
051H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
051H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
051H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
075H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
075H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
075H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
077H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
077H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
077H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
080H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
080H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
080H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
100H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	-	5.61	5.61	5.61
100H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	-	5.61	5.61	5.61
100H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	-	5.61	5.61	5.61
120H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
120H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
120H8- *T5D	575/3/60	-	-	-	-	-	-	-	-
150H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
150H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
150H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
200H8- *T3D	208-230/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
200H8- *T4D	460/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
200H8- *T5D	575/3/60	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61

- = Non-compliant model

Annual Walk-In Energy Factor Ratings - COPELAND - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Unit Model KESA	Power Supply	Outdoor Models			Indoor Models		
		R404A	R407A	R448A	R404A	R407A	R448A
		R507		R449A	R507		R449A
035L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
035L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
035L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
040L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
040L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
040L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
060L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
060L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
060L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	-	2.40
061L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
061L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
061L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
075L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
075L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
075L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
090L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
090L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
090L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
100L 6/8- *T3D	208-230/3/60	3.15	3.15	3.15	2.40	2.40	2.40
100L 6/8- *T4D	460/3/60	3.15	3.15	3.15	2.40	2.40	2.40
100L 6/8- *T5D	575/3/60	3.15	3.15	3.15	2.40	2.40	2.40
120L 6/8- *T3D	208/230/3/60	3.15	3.15	3.15	-	-	-
120L 6/8- *T4D	460/3/60	3.15	3.15	3.15	-	-	-
120L 6/8- *T5D	575/3/60	3.15	3.15	3.15	-	-	-
130L 6/8- *T3D	208/230/3/60	3.15	3.15	3.15	-	-	-
130L 6/8- *T4D	460/3/60	3.15	3.15	3.15	-	-	-
130L 6/8- *T5D	575/3/60	3.15	3.15	3.15	-	-	-
150L 6/8- *T3D	208/230/3/60	3.15	3.15	3.15	-	-	-
150L 6/8- *T4D	460/3/60	3.15	3.15	3.15	-	-	-
150L 6/8- *T5D	575/3/60	3.15	3.15	3.15	-	-	-
220L 6/8- *T3D	208/230/3/60	3.15	3.15	3.15	-	-	-
220L 6/8- *T4D	460/3/60	3.15	3.15	3.15	-	-	-
220L 6/8- *T5D	575/3/60	3.15	3.15	3.15	-	-	-

- = Non-compliant model



web: www.k-rp.com/kes
 email: smcu@k-rp.com
 call: 1-844-893-3222 x521

Annual Walk-In Energy Factor Ratings - BITZER - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Unit Model KESB	Power Supply	Outdoor Models				Indoor Models			
		R404A R507	R407A	R448A R449A	R407C	R404A R507	R407A	R448A R449A	R407C
030H8- * S2D	208-230/1/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
030H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
030H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
030H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
035H8- * S2D	208-230/1/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
035H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
035H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
035H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
040H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
040H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
040H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
050H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
050H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
050H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
060H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
060H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
060H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
076H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
076H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
076H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
090H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
090H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
090H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
100H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
100H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
100H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
120H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
120H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
120H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
150H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
150H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
150H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
200H8- * T3D	208-230/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
200H8- * T4D	460/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61
200H8- * T5D	575/3/60	7.61	7.61	7.61	7.61	5.61	5.61	5.61	5.61

- = Non-compliant model

Annual Walk-In Energy Factor Ratings - BITZER - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Unit Model KESB	Power Supply	Outdoor Models			Indoor Models		
		R404A R507	R407A	R448A R449A	R404A R507	R407A	R448A R449A
030L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
030L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
030L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
031L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
031L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
031L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
039L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
039L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
039L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
050L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
050L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
050L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
060L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
060L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
060L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
080L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
080L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
080L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
100L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
100L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
100L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4
120L 6/8- * T3D	208-230/3/60	3.15	3.15	3.15	2.4	2.4	2.4
120L 6/8- * T4D	460/3/60	3.15	3.15	3.15	2.4	2.4	2.4
120L 6/8- * T5D	575/3/60	3.15	3.15	3.15	2.4	2.4	2.4

- = Non-compliant model

web: www.k-rp.com/kes
 email: smcu@k-rp.com
 call: 1-844-893-3222 x521

Annual Walk-In Energy Factor Ratings - High and Medium Temperature Models

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KQ	Power Supply	Outdoor Models				
		R404A R507	R407A	R448A R449A	R407C	
KQHA006H8-H	S2D	208-230/1/60	7.6	-	7.6	-
KQZA007H8-H	S2D	208-230/1/60	7.6	7.6	7.6	-
	T3D	208-230/3/60	7.6	7.6	7.6	-
KQZA008H8-H	S2D	208-230/1/60	7.6	7.6	7.6	-
	T3D	208-230/3/60	7.6	7.6	7.6	-
KQZA009H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
KQZA010H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA011H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA015H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA020H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA025H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA030H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA035H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA040H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA045H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA050H8-H	S2D	208-230/1/60	7.6	7.6	7.6	7.6
	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6
KQZA060H8-H	T3D	208-230/3/60	7.6	7.6	7.6	7.6
	T4D	460/3/60	7.6	7.6	7.6	7.6

- = Non-compliant model



web: www.k-rp.com/kqz
 email: smcu@k-rp.com
 call: 1-844-893-3222 x521

Annual Walk-In Energy Factor Ratings - Low Temperature Models

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Model KQ	Power Supply	Outdoor Models			
		R404A R507	R407A	R448A R449A	
KQZA008L8-H	S2D	208-230/1/60	2.89	-	-
	T3D	208-230/3/60	2.89	-	-
	T4D	460/3/60	2.89	-	-
KQZA010L8-H	S2D	208-230/1/60	2.94	2.93	2.93
	T3D	208-230/3/60	2.94	2.93	2.93
	T4D	460/3/60	2.94	2.93	2.93
KQZA015L8-H	S2D	208-230/1/60	2.99	2.97	2.98
	T3D	208-230/3/60	2.99	2.97	2.98
	T4D	460/3/60	2.99	2.97	2.98
KQZA020L8-H	S2D	208-230/1/60	3.12	3.11	3.11
	T3D	208-230/3/60	3.12	3.11	3.11
	T4D	460/3/60	3.12	3.11	3.11
KQZA025L8-H	S2D	208-230/1/60	3.15	3.13	3.14
	T3D	208-230/3/60	3.15	3.13	3.14
	T4D	460/3/60	3.15	3.13	3.14
KQZA030L8-H	S2D	208-230/1/60	3.15	3.15	3.15
	T3D	208-230/3/60	3.15	3.15	3.15
	T4D	460/3/60	3.15	3.15	3.15
KQZA035L8-H	S2D	208-230/1/60	3.15	3.15	3.15
	T3D	208-230/3/60	3.15	3.15	3.15
	T4D	460/3/60	3.15	3.15	3.15
KQZA045L8-H	S2D	208-230/1/60	3.15	3.15	3.15
	T3D	208-230/3/60	3.15	3.15	3.15
	T4D	460/3/60	3.15	3.15	3.15
KQZA055L8-H	S2D	208-230/1/60	3.15	3.15	3.15
	T3D	208-230/3/60	3.15	3.15	3.15
	T4D	460/3/60	3.15	3.15	3.15
KQZA060L8-H	T3D	208-230/3/60	3.15	3.15	3.15
	T4D	460/3/60	3.15	3.15	3.15

- = Non-compliant model



web: www.k-rp.com/kqz
email: smcu@k-rp.com
call: 1-844-893-3222 x521

COPELAND SEMI-HERMETIC COMPRESSOR MODELS
Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS075H8-A	7.6		7.6	7.6	7.6
KMS076H8-A	7.6		7.6	7.6	7.6
KMS080H8-A	7.6		7.6	7.6	7.6
KMS100H8-A	7.6		7.6	7.6	7.6
KMS120H8-A	7.6		7.6	7.6	7.6
KMS150H8-A	7.6		7.6	7.6	7.6
KMS200H8-A	7.6		7.6	7.6	7.6
KMD150H8-A	7.6		7.6	7.6	7.6
KMD151H8-A	7.6		7.6	7.6	7.6
KMD160H8-A	7.6		7.6	7.6	7.6
KMD200H8-A	7.6		7.6	7.6	7.6
KMD240H8-A	7.6		7.6	7.6	7.6
KMD300H8-A	7.6		7.6	7.6	7.6
KMD400H8-A	7.6		7.6	7.6	7.6

— = Non-compliant model

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS075M8-A	7.6		7.6	7.6	7.6
KMS076M8-A	7.6		7.6	7.6	7.6
KMS080M8-A	7.6		7.6	7.6	7.6
KMS100M8-A	7.6		7.6	7.6	7.6
KMS120M8-A	7.6		7.6	7.6	7.6
KMS150M8-A	7.6		7.6	7.6	7.6
KMS200M8-A	7.6		7.6	7.6	7.6
KMD150M8-A	7.6		7.6	7.6	7.6
KMD151M8-A	7.6		7.6	7.6	7.6
KMD160M8-A	7.6		7.6	7.6	7.6
KMD200M8-A	7.6		7.6	7.6	7.6
KMD240M8-A	7.6		7.6	7.6	7.6
KMD300M8-A	7.6		7.6	7.6	7.6
KMD400M8-A	7.6		7.6	7.6	7.6

— = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model:
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS075L*-A	3.15		3.15	3.15	—
KMS090L*-A	3.15		3.15	3.15	—
KMS100L*-A	3.15		3.15	3.15	—
KMS120L*-A	3.15		3.15	3.15	—
KMS130L*-A	3.15		3.15	3.15	—
KMS150L*-A	3.15		3.15	3.15	—
KMS220L*-A	3.15		3.15	3.15	—
KMD150L*-A	3.15		3.15	3.15	—
KMD180L*-A	3.15		3.15	3.15	—
KMD200L*-A	3.15		3.15	3.15	—
KMD240L*-A	3.15		3.15	3.15	—
KMD260L*-A	3.15		3.15	3.15	—
KMD300L*-A	3.15		3.15	3.15	—
KMD440L*-A	3.15		3.15	3.15	—

— = Non-compliant model

web: www.k-rp.com/km
 email: mdcu-lgcu@k-rp.com
 call: 1-844-893-3222 x522

BITZER SEMI-HERMETIC COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS060H8-B	7.6		7.6	7.6	7.6
KMS075H8-B	7.6		7.6	7.6	7.6
KMS090H8-B	7.6		7.6	7.6	7.6
KMS100H8-B	7.6		7.6	7.6	7.6
KMS120H8-B	7.6		7.6	7.6	7.6
KMS150H8-B	7.6		7.6	7.6	7.6
KMS200H8-B	7.6		7.6	7.6	7.6
KMD120H8-B	7.6		7.6	7.6	7.6
KMD150H8-B	7.6		7.6	7.6	7.6
KMD180H8-B	7.6		7.6	7.6	7.6
KMD200H8-B	7.6		7.6	7.6	7.6
KMD240H8-B	7.6		7.6	7.6	7.6
KMD300H8-B	7.6		7.6	7.6	7.6
KMD400H8-B	7.6		7.6	7.6	7.6

— = Non-compliant model

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS060M8-B	7.6		7.6	7.6	7.6
KMS075M8-B	7.6		7.6	7.6	7.6
KMS090M8-B	7.6		7.6	7.6	7.6
KMS100M8-B	7.6		7.6	7.6	7.6
KMS120M8-B	7.6		7.6	7.6	7.6
KMS150M8-B	7.6		7.6	7.6	7.6
KMS200M8-B	7.6		7.6	7.6	7.6
KMD120M8-B	7.6		7.6	7.6	7.6
KMD150M8-B	7.6		7.6	7.6	7.6
KMD180M8-B	7.6		7.6	7.6	7.6
KMD200M8-B	7.6		7.6	7.6	7.6
KMD240M8-B	7.6		7.6	7.6	7.6
KMD300M8-B	7.6		7.6	7.6	7.6
KMD400M8-B	7.6		7.6	7.6	7.6

— = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS080L*-B	3.15		3.15	3.15	—
KMS100L*-B	3.15		3.15	3.15	—
KMS120L*-B	3.15		3.15	3.15	—
KMS130L*-B	3.15		3.15	3.15	—
KMS150L*-B	3.15		3.15	3.15	—
KMS200L*-B	3.15		3.15	3.15	—
KMD160L*-B	3.15		3.15	3.15	—
KMD200L*-B	3.15		3.15	3.15	—
KMD240L*-B	3.15		3.15	3.15	—
KMD260L*-B	3.15		3.15	3.15	—
KMD300L*-B	3.15		3.15	3.15	—
KMD400L*-B	3.15		3.15	3.15	—
KMD300L*-A	3.15		3.15	3.15	—
KMD440L*-A	3.15		3.15	3.15	—

— = Non-compliant model

web: www.k-rp.com/km
 email: mdcu-lgcu@k-rp.com
 call: 1-844-893-3222 x522

COPELAND SCROLL COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS050H8-Z	7.6		7.6	7.6	-
KMS060H8-Z	7.6		7.6	7.6	7.6
KMS061H8-Z	7.6		7.6	7.6	7.6
KMS070H8-Z	7.6		7.6	7.6	-
KMS076H8-Z	7.6		7.6	7.6	7.6
KMS085H8-Z	7.6		7.6	7.6	7.6
KMS110H8-Z	7.6		7.6	7.6	7.6
KMS150H8-Z	7.6		7.6	7.6	7.6
KMD100H8-Z	7.6		7.6	7.6	-
KMD120H8-Z	7.6		7.6	7.6	7.6
KMD121H8-Z	7.6		7.6	7.6	7.6
KMD140H8-Z	7.6		7.6	7.6	-
KMD151H8-Z	7.6		7.6	7.6	7.6
KMD170H8-Z	7.6		7.6	7.6	7.6
KMD220H8-Z	7.6		7.6	7.6	7.6
KMD300H8-Z	7.6		7.6	7.6	7.6

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS050M8-Z	7.6		7.6	7.6	7.6
KMS060M8-Z	7.6		7.6	7.6	7.6
KMS061M8-Z	7.6		7.6	7.6	7.6
KMS070M8-Z	7.6		7.6	7.6	7.6
KMS076M8-Z	7.6		7.6	7.6	7.6
KMS085M8-Z	7.6		7.6	7.6	7.6
KMS110M8-Z	7.6		7.6	7.6	7.6
KMS150M8-Z	7.6		7.6	7.6	7.6
KMD100M8-Z	7.6		7.6	7.6	7.6
KMD120M8-Z	7.6		7.6	7.6	7.6
KMD121M8-Z	7.6		7.6	7.6	7.6
KMD140M8-Z	7.6		7.6	7.6	7.6
KMD151M8-Z	7.6		7.6	7.6	7.6
KMD170M8-Z	7.6		7.6	7.6	7.6
KMD220M8-Z	7.6		7.6	7.6	7.6
KMD300M8-Z	7.6		7.6	7.6	7.6

— = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model:
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KMS060L8-Z	3.15		3.15	3.15	-
KMS075L8-Z	3.15		3.15	3.15	-
KMS085L8-Z	3.15		3.15	3.15	-
KMS100L8-Z	3.15		3.15	3.15	-
KMS130L8-Z	3.15		3.15	3.15	-
KMS150L8-Z	3.15		3.15	3.15	-
KMS170L8-Z	3.15		3.15	3.15	-
KMD120L8-Z	3.15		3.15	3.15	-
KMD150L8-Z	3.15		3.15	3.15	-
KMD170L8-Z	3.15		3.15	3.15	-
KMD200L8-Z	3.15		3.15	3.15	-
KMD260L8-Z	3.15		3.15	3.15	-
KMD300L8-Z	3.15		3.15	3.15	-
KMD340L8-Z	3.15		3.15	3.15	-

— = Non-compliant model

web: www.k-rp.com/km
 email: mdcu-lgcu@k-rp.com
 call: 1-844-893-3222 x522

COPELAND COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models			
	R404A	R407A	R448A	R470C
	R507		R449A	
KVS015H8-A	7.6	7.6	7.6	-
KVS020H8-A	7.6	7.6	7.6	7.6
KVS022H8-A	7.6	7.6	7.6	7.6
KVS025H8-A	7.6	7.6	7.6	7.6
KVS030H8-A	7.6	7.6	7.6	7.6
KVS035H8-A	7.6	7.6	7.6	-
KVS040H8-A	7.6	7.6	7.6	7.6
KVD030H8-A	7.6	7.6	7.6	-
KVD040H8-A	7.6	7.6	7.6	7.6
KVD044H8-A	7.6	7.6	7.6	7.6
KVD050H8-A	7.6	7.6	7.6	7.6
KVD060H8-A	7.6	7.6	7.6	7.6
KVD070H8-A	7.6	7.6	7.6	-
KVD080H8-A	7.6	7.6	7.6	7.6
KVS015M8-A	7.6	7.6	7.6	7.6
KVS020M8-A	7.6	7.6	7.6	7.6
KVS022M8-A	7.6	7.6	7.6	7.6
KVS025M8-A	7.6	7.6	7.6	7.6
KVS030M8-A	7.6	7.6	7.6	7.6
KVS035M8-A	7.6	7.6	7.6	7.6
KVS040M8-A	7.6	7.6	7.6	7.6
KVS050M8-A	7.6	7.6	7.6	7.6
KVD030M8-A	7.6	7.6	7.6	7.6
KVD040M8-A	7.6	7.6	7.6	7.6
KVD044M8-A	7.6	7.6	7.6	7.6
KVD050M8-A	7.6	7.6	7.6	7.6
KVD060M8-A	7.6	7.6	7.6	7.6
KVD070M8-A	7.6	7.6	7.6	7.6
KVD080M8-A	7.6	7.6	7.6	7.6
KVD100M8-A	7.6	7.6	7.6	7.6

— = Non-compliant model



web: www.k-rp.com/kv
 email: mdcu-lgcu@k-rp.com
 call: 1-844-893-3222 x522

BITZER COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models			
	R404A	R407A	R448A	R407C
	R507		R449A	
KVS015H8-B	7.6	7.6	7.6	-
KVS020H8-B	7.6	7.6	7.6	7.6
KVS025H8-B	7.6	7.6	7.6	7.6
KVS030H8-B	7.6	7.6	7.6	7.6
KVS035H8-B	7.6	7.6	7.6	7.6
KVS040H8-B	7.6	7.6	7.6	7.6
KVD030H8-B	7.6	7.6	7.6	-
KVD040H8-B	7.6	7.6	7.6	7.6
KVD050H8-B	7.6	7.6	7.6	7.6
KVD060H8-B	7.6	7.6	7.6	7.6
KVD070H8-B	7.6	7.6	7.6	7.6
KVD080H8-B	7.6	7.6	7.6	7.6
KVS015M8-B	7.6	7.6	7.6	-
KVS020M8-B	7.6	7.6	7.6	7.6
KVS025M8-B	7.6	7.6	7.6	7.6
KVS030M8-B	7.6	7.6	7.6	7.6
KVS035M8-B	7.6	7.6	7.6	7.6
KVS040M8-B	7.6	7.6	7.6	7.6
KVS050M8-B	7.6	7.6	7.6	7.6
KVD030M8-B	7.6	7.6	7.6	-
KVD040M8-B	7.6	7.6	7.6	7.6
KVD050M8-B	7.6	7.6	7.6	7.6
KVD060M8-B	7.6	7.6	7.6	7.6
KVD070M8-B	7.6	7.6	7.6	7.6
KVD080M8-B	7.6	7.6	7.6	7.6
KVD100M8-B	7.6	7.6	7.6	7.6

— = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models			
	R404A	R407A	R448A	R407C
	R507		R449A	
KVS012L*-B	-	-	-	-
KVS015L*-B	-	-	-	-
KVS020L*-B	-	-	-	-
KVS025L*-B	-	-	-	-
KVS030L*-B	-	-	-	-
KVS040L*-B	-	-	-	-
KVD024L*-B	-	-	-	-
KVD030L*-B	-	-	-	-
KVD040L*-B	-	-	-	-
KVD050L*-B	-	-	-	-
KVD060L*-B	-	-	-	-
KVD080L*-B	-	-	-	-
KVS012D*-B	3.15	3.15	3.15	-
KVS015D*-B	3.15	3.15	3.15	-
KVS020D*-B	3.15	3.15	3.15	-
KVS025D*-B	3.15	3.15	3.15	-
KVS030D*-B	3.15	3.15	3.15	-
KVS040D*-B	-	-	-	-
KVD024D*-B	3.15	3.15	3.15	-
KVD030D*-B	3.15	3.15	3.15	-
KVD040D*-B	3.15	3.15	3.15	-
KVD050D*-B	3.15	3.15	3.15	-
KVD060D*-B	3.15	3.15	3.15	-
KVD080D*-B	-	-	-	-

— = Non-compliant model

HIGH EFFICIENCY COPELAND COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A R449A	R407C
KVS016H8-A	7.6		7.6	7.6	-
KVS021H8-A	7.6		7.6	7.6	7.6
KVS023H8-A	7.6		7.6	7.6	7.6
KVS026H8-A	7.6		7.6	7.6	7.6
KVS031H8-A	7.6		7.6	7.6	7.6
KVS036H8-A	7.6		7.6	7.6	-
KVS041H8-A	7.6		7.6	7.6	7.6
KVD031H8-A	7.6		7.6	7.6	-
KVD041H8-A	7.6		7.6	7.6	7.6
KVD045H8-A	7.6		7.6	7.6	7.6
KVD051H8-A	7.6		7.6	7.6	7.6
KVD061H8-A	7.6		7.6	7.6	7.6
KVD071H8-A	7.6		7.6	7.6	-
KVD081H8-A	7.6		7.6	7.6	7.6
KVS016M8-A	7.6		7.6	7.6	-
KVS021M8-A	7.6		7.6	7.6	7.6
KVS023M8-A	7.6		7.6	7.6	7.6
KVS026M8-A	7.6		7.6	7.6	7.6
KVS031M8-A	7.6		7.6	7.6	7.6
KVS036M8-A	7.6		7.6	7.6	-
KVS041M8-A	7.6		7.6	7.6	7.6
KVS051M8-A	7.6		7.6	7.6	7.6
KVD031M8-A	7.6		7.6	7.6	-
KVD041M8-A	7.6		7.6	7.6	7.6
KVD045M8-A	7.6		7.6	7.6	7.6
KVD051M8-A	7.6		7.6	7.6	7.6
KVD061M8-A	7.6		7.6	7.6	7.6
KVD071M8-A	7.6		7.6	7.6	-
KVD081M8-A	7.6		7.6	7.6	7.6
KVD101M8-A	7.6		7.6	7.6	7.6
KVS011L 6/8 -A	-		-	-	-
KVS016L 6/8 -A	-		-	-	-
KVS023L 6/8 -A	-		-	-	-
KVS028L 6/8 -A	-		-	-	-
KVS031L 6/8 -A	-		-	-	-
KVS041L 6/8 -A	-		-	-	-
KVD021L 6/8 -A	-		-	-	-
KVD031L 6/8 -A	-		-	-	-
KVD045L 6/8 -A	-		-	-	-
KVD055L 6/8 -A	-		-	-	-
KVD061L 6/8 -A	-		-	-	-
KVD081L 6/8 -A	-		-	-	-
KVS011D 6/8 -A	3.15		3.15	3.15	-
KVS016D 6/8 -A	3.15		3.15	3.15	-
KVS023D 6/8 -A	3.15		3.15	3.15	-
KVS028D 6/8 -A	3.15		3.15	3.15	-
KVS031D 6/8 -A	-		3.15	3.15	-
KVS041D 6/8 -A	-		-	-	-
KVD021D 6/8 -A	3.15		3.15	3.15	-
KVD031D 6/8 -A	3.15		3.15	3.15	-
KVD045D 6/8 -A	3.15		3.15	3.15	-
KVD055D 6/8 -A	3.15		3.15	3.15	-
KVD061D 6/8 -A	-		3.15	3.15	-
KVD081D 6/8 -A	-		-	-	-

— = Non-compliant model

web: www.k-rp.com/kv
 email: mdcu-lgcu@k-rp.com
 call: 1-844-893-3222 x522

HIGH EFFICIENCY BITZER COMPRESSOR MODELS

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models			
	R404A	R407A	R448A	R407C
	R507		R449A	
KVS016H8-B	7.6	7.6	7.6	-
KVS021H8-B	7.6	7.6	7.6	7.6
KVS026H8-B	7.6	7.6	7.6	-
KVS031H8-B	7.6	7.6	7.6	7.6
KVS036H8-B	7.6	7.6	7.6	-
KVS041H8-B	7.6	7.6	7.6	7.6
KVD031H8-B	7.6	7.6	7.6	-
KVD041H8-B	7.6	7.6	7.6	7.6
KVD051H8-B	7.6	7.6	7.6	-
KVD061H8-B	7.6	7.6	7.6	7.6
KVD071H8-B	7.6	7.6	7.6	-
KVD081H8-B	7.6	7.6	7.6	7.6
KVS016M8-B	7.6	7.6	7.6	-
KVS021M8-B	7.6	7.6	7.6	7.6
KVS026M8-B	7.6	7.6	7.6	7.6
KVS031M8-B	7.6	7.6	7.6	7.6
KVS036M8-B	7.6	7.6	7.6	7.6
KVS041M8-B	7.6	7.6	7.6	7.6
KVS051M8-B	7.6	7.6	7.6	7.6
KVD031M8-B	7.6	7.6	7.6	-
KVD041M8-B	7.6	7.6	7.6	7.6
KVD051M8-B	7.6	7.6	7.6	7.6
KVD061M8-B	7.6	7.6	7.6	7.6
KVD071M8-B	7.6	7.6	7.6	7.6
KVD081M8-B	7.6	7.6	7.6	7.6
KVD101M8-B	7.6	7.6	7.6	7.6

— = Non-compliant model

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model:
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models			
	R404A	R407A	R448A	R407C
	R507		R449A	
KVS013L*-B	-	-	-	-
KVS016L*-B	-	-	-	-
KVS021L*-B	-	-	-	-
KVS026L*-B	-	-	-	-
KVS031L*-B	-	-	-	-
KVS041L*-B	-	-	-	-
KVD025L*-B	-	-	-	-
KVD031L*-B	-	-	-	-
KVD041L*-B	-	-	-	-
KVD051L*-B	-	-	-	-
KVD061L*-B	-	-	-	-
KVD081L*-B	-	-	-	-
KVS013D*-B	3.15	3.15	3.15	-
KVS016D*-B	3.15	3.15	3.15	-
KVS021D*-B	3.15	3.15	3.15	-
KVS026D*-B	3.15	3.15	3.15	-
KVS031D*-B	3.15	3.15	3.15	-
KVS041D*-B	-	-	-	-
KVD025D*-B	3.15	3.15	3.15	-
KVD031D*-B	3.15	3.15	3.15	-
KVD041D*-B	3.15	3.15	3.15	-
KVD051D*-B	3.15	3.15	3.15	-
KVD061D*-B	3.15	3.15	3.15	-
KVD081D*-B	-	-	-	-

— = Non-compliant model

AWEF RATINGS

K (ROUNDELL) - HALF ROUND EVAPORATORS

Annual Walk-In Energy Factor Ratings

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model R	R404A R507	R407A	R448A R449A
395	9.00	9.00	9.00
495	9.00	9.00	9.00
650	9.00	9.00	9.00
840	9.00	9.00	9.00
945	9.00	9.00	9.00
1100	9.00	9.00	9.00
1270	9.00	9.00	9.00
2150	9.00	9.00	9.00



AWEF RATINGS

KTM - TWO-WAY EVAPORATORS

Annual Walk-In Energy Factor Ratings - Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KTM	R404A R507	R407A R407C	R448A R449A
207M	9.00	9.00	9.00
209M	9.00	9.00	9.00
313M	9.00	9.00	9.00
215M	9.00	9.00	9.00
318M	9.00	9.00	9.00
321M	9.00	9.00	9.00
426M	9.00	9.00	9.00
531M	9.00	9.00	9.00



Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Model KTM	R404A R507	R407A	R448A R449A
204L	3.95	3.95	3.95
206L	3.98	3.98	3.98
309L	4.01	4.01	4.01
212L	4.05	4.05	4.05
315L	4.09	4.09	4.09
318L	4.12	4.12	4.12
422L	4.15	4.15	4.15
526L	4.15	4.15	4.15

AWEF RATINGS

KLV - LOW VELOCITY EVAPORATORS

Annual Walk-In Energy Factor Ratings

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KLV	R404A	R407A	R448A
	R507	R407C	R449A
106	9.00	9.00	9.00
109	9.00	9.00	9.00
212	9.00	9.00	9.00
217	9.00	9.00	9.00
325	9.00	9.00	9.00
331	9.00	9.00	9.00
437	9.00	9.00	9.00
441	9.00	9.00	9.00
546	9.00	9.00	9.00



web: www.k-rp.com/klv
email: evaps@k-rp.com
call: 1-844-893-3222 x520

AWEF RATINGS

KLP - LOW PROFILE EVAPORATORS

Annual Walk-In Energy Factor Ratings - Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KLP	R404A	R407A	R448A
	R507	R407C	R449A
104M	9.00	9.00	9.00
106M	9.00	9.00	9.00
107M	9.00	9.00	9.00
209M	9.00	9.00	9.00
211M	9.00	9.00	9.00
214M	9.00	9.00	9.00
317M	9.00	9.00	9.00
320M	9.00	9.00	9.00
422M	9.00	9.00	9.00
427M	9.00	9.00	9.00
534M	9.00	9.00	9.00
640M	9.00	9.00	9.00



web: www.k-rp.com/klp
email: evaps@k-rp.com
call: 1-844-893-3222 x520

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Generation "D" Model KLP	R404A	R407A	R448A
	R507		R449A
104L	3.96	3.96	3.96
105L	3.97	3.97	3.97
106L	3.99	3.99	3.99
207L	3.99	3.99	3.99
209L	4.02	4.02	4.02
211L	4.04	4.04	4.04
314L	4.07	4.07	4.07
316L	4.10	4.10	4.10
418L	4.13	4.13	4.13
421L	4.15	4.15	4.15
526L	4.15	4.15	4.15
631L	4.15	4.15	4.15

Generation "D" Model KLP	R404A	R407A	R448A
	R507		R449A
103V	3.95	3.95	3.95
104V	3.96	3.96	3.96
106V	3.98	3.98	3.98
207V	3.99	3.99	3.99
208V	4.01	4.01	4.01
211V	4.04	4.04	4.04
313V	4.06	4.06	4.06
316V	4.10	4.10	4.10
418V	4.13	4.13	4.13
421V	4.15	4.15	4.15
524V	4.15	4.15	4.15
627V	4.15	4.15	4.15

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KMP	R404A R507	R407A R407C	R448A R449A
120M	9.00	9.00	9.00
124M	9.00	9.00	9.00
232M	9.00	9.00	9.00
240M	9.00	9.00	9.00
248M	9.00	9.00	9.00
360M	9.00	9.00	9.00
372M	9.00	9.00	9.00
486M	9.00	9.00	9.00
495M	9.00	9.00	9.00



web: www.k-rp.com/kmp
email: evaps@k-rp.com
call: **1-844-893-3222 x520**

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Model KMP	R404A R507	R407A	R448A R449A
116L	4.09	4.09	4.09
120L	4.14	4.14	4.14
224L	4.15	4.15	4.15
233L	4.15	4.15	4.15
239L	4.15	4.15	4.15
347L	4.15	4.15	4.15
355L	4.15	4.15	4.15
470L	4.15	4.15	4.15

Model KMP	R404A R507	R407A	R448A R449A
113V	4.06	4.06	4.06
117V	4.11	4.11	4.11
221V	4.15	4.15	4.15
226V	4.15	4.15	4.15
234V	4.15	4.15	4.15
338V	4.15	4.15	4.15
349V	4.15	4.15	4.15
457V	4.15	4.15	4.15

Annual Walk-In Energy Factor Ratings - High/Medium Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in cooler applications."

Model KEP	R404A R507	R407A R407C	R448A R449A
031H	9.00	9.00	9.00
036H	9.00	9.00	9.00
055H	9.00	9.00	9.00
061H	9.00	9.00	9.00
072H	9.00	9.00	9.00
094H	9.00	9.00	9.00
109H	9.00	9.00	9.00
135H	9.00	9.00	9.00

Model KEP	R404A R507	R407A R407C	R448A R449A
029M	9.00	9.00	9.00
034M	9.00	9.00	9.00
051M	9.00	9.00	9.00
057M	9.00	9.00	9.00
068M	9.00	9.00	9.00
088M	9.00	9.00	9.00
101M	9.00	9.00	9.00
125M	9.00	9.00	9.00

Annual Walk-In Energy Factor Ratings - Low Temperature

If a numerical value is listed in the table below, the following statement applies to that corresponding model: "This refrigeration system is designed and certified for use in walk-in freezer applications."

Model KEP	R404A R507	R407A	R448A R449A
025L	4.15	4.15	4.15
030L	4.15	4.15	4.15
038L	4.15	4.15	4.15
050L	4.15	4.15	4.15
060L	4.15	4.15	4.15
075L	4.15	4.15	4.15
089L	4.15	4.15	4.15
108L	4.15	4.15	4.15

Model KEP	R404A R507	R407A	R448A R449A
022V	4.15	4.15	4.15
025V	4.15	4.15	4.15
037V	4.15	4.15	4.15
043V	4.15	4.15	4.15
051V	4.15	4.15	4.15
065V	4.15	4.15	4.15
077V	4.15	4.15	4.15
093V	4.15	4.15	4.15

	<p>web: www.k-rp.com/kep email: evaps@k-rp.com call: 1-844-893-3222 x520</p>
---	--