

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KEZA	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KEZA007H8	7.6	–	7.6	–	–	–	–	–
KEZA008H8	7.6	7.6	7.6	–	–	–	–	–
KEZA009H8	7.6	7.6	7.6	7.6	–	–	–	–
KEZA010H8	7.6	7.6	7.6	–	–	–	–	–
KEZA011H8	7.6	7.6	7.6	–	–	5.61	5.61	–
KEZA015H8	7.6	7.6	7.6	7.6	–	5.61	–	–
KEZA020H8	7.6	7.6	7.6	7.6	–	–	–	–
KEZA025H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA030H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA035H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA040H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA045H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA050H8	7.6	7.6	7.6	7.6	–	5.61	5.61	5.61
KEZA060H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA061H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA070H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA076H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA076H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA085H8	7.6	7.6	7.6	7.6	–	5.61	5.61	5.61
KEZA110H8	7.6	7.6	7.6	7.6	5.61	5.61	5.61	5.61
KEZA150H8	7.6	7.6	7.6	7.6	–	–	5.61	5.61

– = Non-compliant model For R449A, use R448A data.

**Annual Walk-In Energy Factor Ratings - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KEZA	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KEZA008L8	2.88	2.87	2.88	–	–	–	–	–
KEZA010L8	2.93	2.91	2.92	–	–	–	–	–
KEZA015L8	2.97	2.94	2.96	–	–	–	–	–
KEZA020L8	3.08	3.06	3.07	–	–	–	–	–
KEZA025L8	3.15	3.15	3.15	–	–	–	–	–
KEZA030L8	3.15	3.15	3.15	–	–	–	–	–
KEZA035L8	3.15	3.15	3.15	–	–	–	–	–
KEZA045L8	3.15	3.15	3.15	–	2.4	–	–	–
KEZA055L8	3.15	3.15	3.15	–	2.4	–	–	–
KEZA060L8	3.15	3.15	3.15	–	2.4	–	–	–
KEZA075L8	3.15	3.15	3.15	–	2.4	–	–	–
KEZA085L8	3.15	3.15	3.15	–	2.4	–	–	–
KEZA100L8	3.15	3.15	3.15	–	2.4	–	2.4	–
KEZA130L8	3.15	3.15	3.15	–	2.4	–	2.4	–
KEZA150L8	3.15	3.15	3.15	–	2.4	–	2.4	–
KEZA170L8	3.15	3.15	3.15	–	2.4	–	2.4	–

– = Non-compliant model For R449A, use R448A data.

web: [www.k-rp.com/kez](http://www.k-rp.com/kez)  
 email: [smcu@k-rp.com](mailto:smcu@k-rp.com)  
 call: 1-844-893-3222 x521

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KEH	Outdoor Models			Indoor Models		
	R404A R507	R407A	R448A	R404A R507	R407A	R448A
KEHT006M8	7.60	–	–	–	–	–
KEHA015M8	7.60	7.60	7.60	–	–	–
KEHA020M8	7.60	7.60	7.60	–	–	–
KEHA025M8	7.60	7.60	7.60	5.61	5.61	5.61
KEHA030M8	7.60	7.60	7.60	5.61	–	5.61
KEHA035M8	7.60	7.60	7.60	5.61	–	5.61

– = Non-compliant model  
For R449A, use R448A data.

**Annual Walk-In Energy Factor Ratings - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KEH	Outdoor Models			Indoor Models		
	R404A R507	R407A	R448A	R404A R507	R407A	R448A
KEHA006L6	2.83	–	–	–	–	–
KEHA008L6	2.85	–	–	–	–	–
KEHA010L6	2.88	–	–	–	–	–
KEHA015L6	2.96	–	–	–	–	–
KEHA020L6	2.97	–	–	–	–	–
KEHA025L6	3.12	–	–	–	–	–

– = Non-compliant model  
For R449A, use R448A data.



web: [www.k-rp.com/keh](http://www.k-rp.com/keh)  
 email: [smcu@k-rp.com](mailto:smcu@k-rp.com)  
 call: 1-844-893-3222 x521

**Annual Walk-In Energy Factor Ratings - COPELAND - High/Medium Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KESA	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KESA050H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA051H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA075H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA077H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA080H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA100H8	7.60	7.60	7.60	7.60	-	5.61	5.61	5.61
KESA120H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA150H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESA200H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61

- = Non-compliant model  
For R449A, use R448A data.

**Annual Walk-In Energy Factor Ratings - COPELAND - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KESA	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KESA035L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA040L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA060L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA061L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA075L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA090L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA100L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA120L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA130L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA150L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-
KESA220L 6/8	3.15	3.15	3.15	-	2.4	2.4	2.4	-

- = Non-compliant model  
For R449A, use R448A data.



web: [www.k-rp.com/kes](http://www.k-rp.com/kes)  
 email: [smcu@k-rp.com](mailto:smcu@k-rp.com)  
 call: 1-844-893-3222 x521

**Annual Walk-In Energy Factor Ratings - BITZER - High/Medium Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KESB	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KESB030H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB035H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB040H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB050H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB060H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB076H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB090H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB100H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB120H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB150H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61
KESB200H8	7.60	7.60	7.60	7.60	5.61	5.61	5.61	5.61

– = Non-compliant model  
For R449A, use R448A data.

**Annual Walk-In Energy Factor Ratings - BITZER - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model: " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KESB	Outdoor Models				Indoor Models			
	R404A R507	R407A	R448A	R407C	R404A R507	R407A	R448A	R407C
KESB030L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB031L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB039L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB050L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB060L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB080L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB100L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–
KESB120L 6/8	3.15	3.15	3.15	–	2.4	2.4	2.4	–

– = Non-compliant model  
For R449A, use R448A data.

web: [www.k-rp.com/kes](http://www.k-rp.com/kes)  
 email: [smcu@k-rp.com](mailto:smcu@k-rp.com)  
 call: 1-844-893-3222 x521

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model KQZ	Outdoor Models			
	R404A R507	R407A	R448A *	R407C
KQZA007H8	7.6	-	7.6	-
KQZA008H8	7.6	7.6	7.6	-
KQZA009H8	7.6	7.6	7.6	-
KQZA010H8	7.6	7.6	7.6	-
KQZA011H8	7.6	7.6	7.6	-
KQZA015H8	7.6	7.6	7.6	7.6
KQZA020H8	7.6	7.6	7.6	7.6
KQZA025H8	7.6	7.6	7.6	7.6
KQZA030H8	7.6	7.6	7.6	7.6
KQZA035H8	7.6	7.6	7.6	7.6
KQZA040H8	7.6	7.6	7.6	7.6
KQZA050H8	7.6	7.6	7.6	7.6
KQZA060H8	7.6	7.6	7.6	7.6

— = Non-compliant model      \* For R449A, use R448A data.

**Annual Walk-In Energy Factor Ratings - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model:  
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model KQZ	Outdoor Models			
	R404A R507	R407A	R448A *	R407C
KQZA008L8	2.87	2.87	2.88	-
KQZA010L8	2.92	2.91	2.92	-
KQZA015L8	2.96	2.94	2.96	-
KQZA020L8	3.07	3.03	3.04	-
KQZA025L8	3.11	3.08	3.09	-
KQZA030L8	3.15	3.15	3.15	-
KQZA035L8	3.15	3.15	3.15	-
KQZA045L8	3.15	3.15	3.15	-
KQZA055L8	3.15	3.15	3.15	-
KQZA060L8	3.15	3.15	3.15	-

— = Non-compliant model      \* For R449A, use R448A data.

web: [www.k-rp.com/kqz](http://www.k-rp.com/kqz)  
 email: [smcu@k-rp.com](mailto:smcu@k-rp.com)  
 call: 1-844-893-3222 x521

**COPELAND COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS075H8-A	7.6		7.6	7.6	7.6
KMS076H8-A	7.6		7.6	7.6	7.6
KMS080H8-A	7.6		7.6	7.6	7.6
KMS100H8-A	7.6		7.6	7.6	7.6
KMS120H8-A	7.6		7.6	7.6	7.6
KMS150H8-A	7.6		7.6	7.6	7.6
KMS200H8-A	7.6		7.6	7.6	7.6
KMD150H8-A	7.6		7.6	7.6	7.6
KMD151H8-A	7.6		7.6	7.6	7.6
KMD160H8-A	7.6		7.6	7.6	7.6
KMD200H8-A	7.6		7.6	7.6	7.6
KMD240H8-A	7.6		7.6	7.6	7.6
KMD300H8-A	7.6		7.6	7.6	7.6
KMD400H8-A	7.6		7.6	7.6	7.6

— = Non-compliant model

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS075M8-A	7.6		7.6	7.6	7.6
KMS076M8-A	7.6		7.6	7.6	7.6
KMS080M8-A	7.6		7.6	7.6	7.6
KMS100M8-A	7.6		7.6	7.6	7.6
KMS120M8-A	7.6		7.6	7.6	7.6
KMS150M8-A	7.6		7.6	7.6	7.6
KMS200M8-A	7.6		7.6	7.6	7.6
KMD150M8-A	7.6		7.6	7.6	7.6
KMD151M8-A	7.6		7.6	7.6	7.6
KMD160M8-A	7.6		7.6	7.6	7.6
KMD200M8-A	7.6		7.6	7.6	7.6
KMD240M8-A	7.6		7.6	7.6	7.6
KMD300M8-A	7.6		7.6	7.6	7.6
KMD400M8-A	7.6		7.6	7.6	7.6

— = Non-compliant model

**Annual Walk-In Energy Factor Ratings - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model:  
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS075L*-A	3.15		3.15	3.15	—
KMS090L*-A	3.15		3.15	3.15	—
KMS100L*-A	3.15		3.15	3.15	—
KMS120L*-A	3.15		3.15	3.15	—
KMS130L*-A	3.15		3.15	3.15	—
KMS150L*-A	3.15		3.15	3.15	—
KMS220L*-A	3.15		3.15	3.15	—
KMD150L*-A	3.15		3.15	3.15	—
KMD180L*-A	3.15		3.15	3.15	—
KMD200L*-A	3.15		3.15	3.15	—
KMD240L*-A	3.15		3.15	3.15	—
KMD260L*-A	3.15		3.15	3.15	—
KMD300L*-A	3.15		3.15	3.15	—
KMD440L*-A	3.15		3.15	3.15	—

— = Non-compliant model

web: [www.k-rp.com/km](http://www.k-rp.com/km)  
 email: [mdcu-lgcu@k-rp.com](mailto:mdcu-lgcu@k-rp.com)  
 call: 1-844-893-3222 x522

**BITZER COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS060H8-B	7.6		7.6	7.6	7.6
KMS075H8-B	7.6		7.6	7.6	7.6
KMS090H8-B	7.6		7.6	7.6	7.6
KMS100H8-B	7.6		7.6	7.6	7.6
KMS120H8-B	7.6		7.6	7.6	7.6
KMS150H8-B	7.6		7.6	7.6	7.6
KMS200H8-B	7.6		7.6	7.6	7.6
KMD120H8-B	7.6		7.6	7.6	7.6
KMD150H8-B	7.6		7.6	7.6	7.6
KMD180H8-B	7.6		7.6	7.6	7.6
KMD200H8-B	7.6		7.6	7.6	7.6
KMD240H8-B	7.6		7.6	7.6	7.6
KMD300H8-B	7.6		7.6	7.6	7.6
KMD400H8-B	7.6		7.6	7.6	7.6

— = Non-compliant model

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS060M8-B	7.6		7.6	7.6	7.6
KMS075M8-B	7.6		7.6	7.6	7.6
KMS090M8-B	7.6		7.6	7.6	7.6
KMS100M8-B	7.6		7.6	7.6	7.6
KMS120M8-B	7.6		7.6	7.6	7.6
KMS150M8-B	7.6		7.6	7.6	7.6
KMS200M8-B	7.6		7.6	7.6	7.6
KMD120M8-B	7.6		7.6	7.6	7.6
KMD150M8-B	7.6		7.6	7.6	7.6
KMD180M8-B	7.6		7.6	7.6	7.6
KMD200M8-B	7.6		7.6	7.6	7.6
KMD240M8-B	7.6		7.6	7.6	7.6
KMD300M8-B	7.6		7.6	7.6	7.6
KMD400M8-B	7.6		7.6	7.6	7.6

— = Non-compliant model

**Annual Walk-In Energy Factor Ratings - Low Temperature**

If a numerical value is listed in the table below, the following statement applies to that corresponding model:  
 " This refrigeration system is designed and certified for use in walk-in freezer applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KMS080L*-B	3.15		3.15	3.15	—
KMS100L*-B	3.15		3.15	3.15	—
KMS120L*-B	3.15		3.15	3.15	—
KMS130L*-B	3.15		3.15	3.15	—
KMS150L*-B	3.15		3.15	3.15	—
KMS200L*-B	3.15		3.15	3.15	—
KMD160L*-B	3.15		3.15	3.15	—
KMD200L*-B	3.15		3.15	3.15	—
KMD240L*-B	3.15		3.15	3.15	—
KMD260L*-B	3.15		3.15	3.15	—
KMD300L*-B	3.15		3.15	3.15	—
KMD400L*-B	3.15		3.15	3.15	—
KMD300L*-A	3.15		3.15	3.15	—
KMD440L*-A	3.15		3.15	3.15	—

— = Non-compliant model

web: [www.k-rp.com/km](http://www.k-rp.com/km)  
 email: [mdu-lgcu@k-rp.com](mailto:mdu-lgcu@k-rp.com)  
 call: 1-844-893-3222 x522

**COPELAND COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KVS015H8-A	7.6		7.6	7.6	-
KVS020H8-A	7.6		7.6	7.6	7.6
KVS022H8-A	7.6		7.6	7.6	7.6
KVS025H8-A	7.6		7.6	7.6	7.6
KVS030H8-A	7.6		7.6	7.6	7.6
KVS035H8-A	7.6		7.6	7.6	-
KVS040H8-A	7.6		7.6	7.6	7.6
KVD030H8-A	7.6		7.6	7.6	-
KVD040H8-A	7.6		7.6	7.6	7.6
KVD044H8-A	7.6		7.6	7.6	7.6
KVD050H8-A	7.6		7.6	7.6	7.6
KVD060H8-A	7.6		7.6	7.6	7.6
KVD070H8-A	7.6		7.6	7.6	-
KVD080H8-A	7.6		7.6	7.6	7.6
KVS015M8-A	7.6		7.6	7.6	7.6
KVS020M8-A	7.6		7.6	7.6	7.6
KVS022M8-A	7.6		7.6	7.6	7.6
KVS025M8-A	7.6		7.6	7.6	7.6
KVS030M8-A	7.6		7.6	7.6	7.6
KVS035M8-A	7.6		7.6	7.6	7.6
KVS040M8-A	7.6		7.6	7.6	7.6
KVS050M8-A	7.6		7.6	7.6	7.6
KVD030M8-A	7.6		7.6	7.6	7.6
KVD040M8-A	7.6		7.6	7.6	7.6
KVD044M8-A	7.6		7.6	7.6	7.6
KVD050M8-A	7.6		7.6	7.6	7.6
KVD060M8-A	7.6		7.6	7.6	7.6
KVD070M8-A	7.6		7.6	7.6	7.6
KVD080M8-A	7.6		7.6	7.6	7.6
KVD100M8-A	7.6		7.6	7.6	7.6

— = Non-compliant model



web: [www.k-rp.com/kv](http://www.k-rp.com/kv)  
 email: [mdcu-lgcu@k-rp.com](mailto:mdcu-lgcu@k-rp.com)  
 call: 1-844-893-3222 x522



**BITZER COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KVS015H8-B	7.6		7.6	7.6	-
KVS020H8-B	7.6		7.6	7.6	7.6
KVS025H8-B	7.6		7.6	7.6	7.6
KVS030H8-B	7.6		7.6	7.6	7.6
KVS035H8-B	7.6		7.6	7.6	7.6
KVS040H8-B	7.6		7.6	7.6	7.6
KVD030H8-B	7.6		7.6	7.6	-
KVD040H8-B	7.6		7.6	7.6	7.6
KVD050H8-B	7.6		7.6	7.6	7.6
KVD060H8-B	7.6		7.6	7.6	7.6
KVD070H8-B	7.6		7.6	7.6	7.6
KVD080H8-B	7.6		7.6	7.6	7.6
KVS015M8-B	7.6		7.6	7.6	-
KVS020M8-B	7.6		7.6	7.6	7.6
KVS025M8-B	7.6		7.6	7.6	7.6
KVS030M8-B	7.6		7.6	7.6	7.6
KVS035M8-B	7.6		7.6	7.6	7.6
KVS040M8-B	7.6		7.6	7.6	7.6
KVS050M8-B	7.6		7.6	7.6	7.6
KVD030M8-B	7.6		7.6	7.6	-
KVD040M8-B	7.6		7.6	7.6	7.6
KVD050M8-B	7.6		7.6	7.6	7.6
KVD060M8-B	7.6		7.6	7.6	7.6
KVD070M8-B	7.6		7.6	7.6	7.6
KVD080M8-B	7.6		7.6	7.6	7.6
KVD100M8-B	7.6		7.6	7.6	7.6

— = Non-compliant model



*web:* [www.k-rp.com/kv](http://www.k-rp.com/kv)  
*email:* [mdcu-lgcu@k-rp.com](mailto:mdcu-lgcu@k-rp.com)  
*call:* 1-844-893-3222 x522

**HIGH EFFICIENCY COPELAND COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KVS016H8-A	7.6		7.6	7.6	-
KVS021H8-A	7.6		7.6	7.6	7.6
KVS023H8-A	7.6		7.6	7.6	7.6
KVS026H8-A	7.6		7.6	7.6	7.6
KVS031H8-A	7.6		7.6	7.6	7.6
KVS036H8-A	7.6		7.6	7.6	-
KVS041H8-A	7.6		7.6	7.6	7.6
KVD031H8-A	7.6		7.6	7.6	-
KVD041H8-A	7.6		7.6	7.6	7.6
KVD045H8-A	7.6		7.6	7.6	7.6
KVD051H8-A	7.6		7.6	7.6	7.6
KVD061H8-A	7.6		7.6	7.6	7.6
KVD071H8-A	7.6		7.6	7.6	-
KVD081H8-A	7.6		7.6	7.6	7.6
KVS016M8-A	7.6		7.6	7.6	-
KVS021M8-A	7.6		7.6	7.6	7.6
KVS023M8-A	7.6		7.6	7.6	7.6
KVS026M8-A	7.6		7.6	7.6	7.6
KVS031M8-A	7.6		7.6	7.6	7.6
KVS036M8-A	7.6		7.6	7.6	-
KVS041M8-A	7.6		7.6	7.6	7.6
KVS051M8-A	7.6		7.6	7.6	7.6
KVD031M8-A	7.6		7.6	7.6	-
KVD041M8-A	7.6		7.6	7.6	7.6
KVD045M8-A	7.6		7.6	7.6	7.6
KVD051M8-A	7.6		7.6	7.6	7.6
KVD061M8-A	7.6		7.6	7.6	7.6
KVD071M8-A	7.6		7.6	7.6	-
KVD081M8-A	7.6		7.6	7.6	7.6
KVD101M8-A	7.6		7.6	7.6	7.6

— = Non-compliant model



web: [www.k-rp.com/kv](http://www.k-rp.com/kv)  
 email: [mdcu-lgcu@k-rp.com](mailto:mdcu-lgcu@k-rp.com)  
 call: 1-844-893-3222 x522

**HIGH EFFICIENCY BITZER COMPRESSOR MODELS**

**Annual Walk-In Energy Factor Ratings - High/Medium Temperature**

If a numerical value is listed in the tables below, the following statement applies to that corresponding model:  
 "This refrigeration system is designed and certified for use in walk-in cooler applications."

Base Unit Model	Outdoor Models				
	R404A	R507	R407A	R448A	R407C
KVS016H8-B	7.6		7.6	7.6	-
KVS021H8-B	7.6		7.6	7.6	7.6
KVS026H8-B	7.6		7.6	7.6	-
KVS031H8-B	7.6		7.6	7.6	7.6
KVS036H8-B	7.6		7.6	7.6	-
KVS041H8-B	7.6		7.6	7.6	7.6
KVD031H8-B	7.6		7.6	7.6	-
KVD041H8-B	7.6		7.6	7.6	7.6
KVD051H8-B	7.6		7.6	7.6	-
KVD061H8-B	7.6		7.6	7.6	7.6
KVD071H8-B	7.6		7.6	7.6	-
KVD081H8-B	7.6		7.6	7.6	7.6
KVS016M8-B	7.6		7.6	7.6	-
KVS021M8-B	7.6		7.6	7.6	7.6
KVS026M8-B	7.6		7.6	7.6	7.6
KVS031M8-B	7.6		7.6	7.6	7.6
KVS036M8-B	7.6		7.6	7.6	7.6
KVS041M8-B	7.6		7.6	7.6	7.6
KVS051M8-B	7.6		7.6	7.6	7.6
KVD031M8-B	7.6		7.6	7.6	-
KVD041M8-B	7.6		7.6	7.6	7.6
KVD051M8-B	7.6		7.6	7.6	7.6
KVD061M8-B	7.6		7.6	7.6	7.6
KVD071M8-B	7.6		7.6	7.6	7.6
KVD081M8-B	7.6		7.6	7.6	7.6
KVD101M8-B	7.6		7.6	7.6	7.6

— = Non-compliant model



web: [www.k-rp.com/kv](http://www.k-rp.com/kv)  
 email: [mdcu-lgcu@k-rp.com](mailto:mdcu-lgcu@k-rp.com)  
 call: 1-844-893-3222 x522